

## JWL weighing scale

- Resolution up to 1/15,000 (standard) or 1/30,000 (optional) or 1/60,000 (optional)
- A/D covered by aluminium plate, prevent PCB from static and moisture
- Weighing platter easy to disassemble (with anti-cockroach design)
- Exports the weighing data to PC in the form of EXCEL
- Overload and transport protection devices
- Zero/ Zero tracking/ Tare/ Weighing/ Simple counting / Accumulation/ Check weighing functions
- Auto shut off/ auto backlight
- Auto printing within OK range
- RS-232/RTC/Relay/Blue Tooth/U-KEY connector/WP wireless print/ U-disk Module/Wifi/Ethernet (optional)
- Ideal for factories, incoming/outgoing goods inspection, inventory management, QC, formulation, general weighing, packaging or other light industrial applications



| Model             | JWL-1.5K  | JWL-3K  | JWL-6K      | JWL-7.5K | JWL-15K     | JWL-30K |
|-------------------|---|---------|-------------|----------|-------------|---------|
| Capacity (kg)     | 1.5   | 3       | 6           | 7.5      | 15          | 30      |
| Division (g)      | 0.1/0.05  | 0.2/0.1 | 0.5/0.2/0.1 | 0.5/0.2  | 0.1/0.5/0.2 | 2/1/0.5 |
| Weighing units    | kg, g, t, lb, oz, pcs   |         |             |          |             |         |
| Display           | 6 digits, 30mm digit height, LCD display with green backlight |         |             |          |             |         |
| Weighing pan (mm) | 294 x 228 (stainless steel)                                   |         |             |          |             |         |
| Weight            | Net weight: 4.72 kg, Gross weight: 5.11 kg                    |         |             |          |             |         |
| Power supply      | AC 110V/220V (AC ±10%) or Rechargeable battery (6V/4Ah)       |         |             |          |             |         |